



PRODUCT SPECIFICATION

R11



INTRODUCTION

The Reacta 11 Sensor is an integrally mounted sensor offering presence detection and remote control programming from ground level using our REA-AP controller. The Reacta 11 Sensor is designed to operate in adverse conditions in temperatures as low as -40°C ensuring it is suitable for environments such as industrial freezers and cold stores as well as external applications. The Reacta 11 is designed to operate between 3M and 15M mounting heights.

FEATURES & BENEFITS

FEATURES

- Mounting Type: Integral
- Wireless: No
- Minimum Mounting Height: 3M
- Maximum Mounting Height: 15M
- Presence Detection: Passive Infra-Red
- Daylight Control: No
- Detection Diameter: 30M At Max Mounting Height
- Output: DALI
- Programmer: REA-AP
- Voltage: 230v 50/60Hz
- Control: Single Driver
- Operating Temperature: -40 to +25°C
- IP Rating: IP65
- Colour: White
- Standby Power: 0.36W

ADJUSTABLE PARAMETERS

- PIR: ON / OFF
- High Time Delay: 30sec to 60min
- Low Light Level: 1-100%
- Low Time Delay: 30sec to 60min / Continuous
- High Light Level: 1-100%
- Fade Rate: 3-300 Seconds
- Power Up State: ON / OFF
- 12 Hour Auto-reset: YES / NO

IMAGES



SENSOR DETECTION

