



# PRODUCT SPECIFICATION

---

R21C



---

## INTRODUCTION

---

The Reacta 21C Sensor is an integrally mounted sensor for batten luminaire such as our Ecopak and Dexpax offering presence detection and Bi-Level Dimming, during periods of occupancy the luminaire will operate at 100% output and dim to 10% output during periods of absence. The Reacta 21C offers an adjustable time delay set via a turn dial on the sensor. Low time delays settings of 10 minutes or 30 minutes can be set via a jumper on the circuit board if required.

---

## FEATURES & BENEFITS

---

### FEATURES

- Mounting Type: Integral
- Wireless: No
- Minimum Mounting Height: 2.5M
- Maximum Mounting Height: 4M
- Presence Detection: Passive Infra-Red
- Daylight Control: No
- Detection Diameter: 8M At Max Mounting Height
- Output: Bi-Level Dimming
- Programmer: Adjustable dials
- Voltage: 230v 50/60Hz
- Control: Single Driver
- Operating Temperature: 0-25°C
- IP Rating: IP20
- Colour: White
- Standby Power: 0.5W

---

## ADJUSTABLE PARAMETERS

---

- High Time Delay: 10sec to 60min
- Low Time delay: 10min / 30min (Set via jumper)

---

## IMAGES

---



SENSOR DETECTION

