



## PRODUCT SPECIFICATION

---

R44



---

## INTRODUCTION

---

The Reacta 44 Sensor is an integrally mounted sensor rated to IP20 offering presence detection, daylight regulation and ground level programming from remote control. Suitable for use between 2.5M and 7M mounting heights the Reacta 44 is ideally suited to applications from offices and academia through to logistics applications when mounted in our Indeco luminaire. A basic controller for local user control is available where there is a requirement for staff to be able to adjust their own lighting. The R44 mini sensor is used with a wide selection of recessed modular and suspended products in our range.

FEATURES & BENEFITS

- **Mounting Type:** Integral
- **Wireless:** No
- **Maximum Mounting Height:** 7m
- **Occupancy Detection:** PIR
- **Daylight Control:** Daylight Regulation
- **Output:** DALI
- **IP Rating:** IP20, IP65 when used in Typhon
- **IP Rating:** IP65
- **Programmer:** REA AP

ADJUSTABLE PARAMETERS

- **Occupied Level:** 1-100%
- **Occupied Time:** up to 60 minutes
- **Transition Time:** up to 60 minutes or forever
- **Transition Level:** 1-100%
- **Daylight Regulation:** Enabled/Disabled
- **Bright Out Mode:** Enabled/Disabled
- **Bright Out Threshold:** Disabled/2-500Lux
- **Daylight Regulation level:** up to 1000Lux
- **PIR:** on/off
- More parameters available on programmer

IMAGES



### SENSOR DETECTION

