



PRODUCT SPECIFICATION

REAF 7 10A LL IP SENSOR



INTRODUCTION

The REAF 7 10A LL IP is a Recessed flush mounted passive infrared occupancy and daylight sensor with fixed output relay control.

FEATURES & BENEFITS

- Mounting Type: Recessed
- Wireless: No
- Maximum Mounting Height: 3.5M
- Occupancy Detection: PIR
- Daylight Control: Bright Out
- Detection Diameter - Micro: 7M at 2.5M mounting height
- Detection Diameter - Macro: 10M at 2.5M mounting height
- Output: Relay
- Programmer: REA-DPA/REA 7 PTH DIR
- Voltage: 230v 50/60Hz
- Control: 10A relay
- IP Rating: IP55
- Colour: White
- Standby Power: 0.15W

APPLICATION

- Shower rooms
- Changing room with showers
- Clean rooms

ADJUSTABLE PARAMETERS

- Detect Occupancy: Yes/No
- Power Up State: Occupied/ unoccupied
- Occ trigger mode: Presence/Absence
- Occupied Timer: 10 seconds - 96 hours
- Photocell: Enabled/disabled
- Set point Low: 0 to 1023
- Set point High: 0 to 1023

More parameters available on programmer


- REA7 PTHDIR
- REA DPA

- REA7 UCHDIR


IMAGES




DIAGRAMS



REAF 7 10A LL IP



SENSOR DETECTION



ORDER CODES

SENSOR

| Code | Description |
|------------------|---|
| REAF 7 10A LL IP | Flush Mounted, Low Level Sensor, 10Amps Switching Relay, Non-Dimming, Manual Override, IP55 |