



PRODUCT SPECIFICATION

REAF 7 10A MW DUAL



INTRODUCTION

The REAF 7 10A MW DUAL is a Semi-flush recessed mounting microwave occupancy sensor with two 10amp load switching relays, the secondary relay can be used for separate switching of a fan or solenoid control.

FEATURES & BENEFITS

- **Mounting Type:** Recessed
- **Wireless:** No
- **Maximum Mounting Height:** 3.5m
- **Occupancy Detection:** Microwave
- **Daylight Control:** Bright Out
- **Output:** On/Off
- **Supply Power Source:** 230V
- **IP Rating:** IP4X
- **Programmer:** REA DPA

ADJUSTABLE PARAMETERS



- **Movement Sensitivity:** Minimum / Very Low / Low, Medium / High / Very high / Maximum
- **Occupied mode:** Presence/Absence/Manual
- **Occupied Time:** up to 12 hours
- **Bright Out Mode:** Enabled/Disabled
- **PIR:** on/off
- More parameters available on programmer

IMAGES




DIAGRAMS


Switch Live Output Connections



Power Connections



Volt-free Output Connections



ORDER CODES

Code	Description
REAF 7 10A MW DUAL	Flush Reacta 7 microwave with dual relay
REA 7 SURFMT	Reacta 7 Surface Mounting Kit