



PRODUCT SPECIFICATION

EXIXL



INTRODUCTION

The EXIXL offers viewing distances of up to 79M providing the ideal solution for applications such as warehouses, factories and airports where standard exit signage does not provide adequate visibility.

The EXIXL is suitable for both top and rear mounting and is available in IP20 and IP65 variants. Low temperature options suitable for ambient temperatures as low as -25°C are available for use in industrial cold stores and freezers. The EXI is supplied with lithium iron phosphate batteries as standard for extended life time and warranty and can be ordered in standard, self test and autotest emergency variants. Central battery compatible variants are available in a range of voltages as well as wireless emergency versions offering compatibility with Reacta-Link and Reacta-Control systems allowing you to automate emergency testing and report failures, minimising the life time maintenance costs of your emergency installation.

**UK
CA** CE IP20 IP65

APPLICATION

- Canteen
- Corridor
- Education
- Food / Clean Area
- Healthcare / Social Housing
- Hotel / Leisure

- Industrial / Manufacturing
- Kitchen
- Office
- Retail
- Stairwell
- Store Room
- Toilet
- Transport
- Warehouse / Storage

SPECIFICATION

CONSTRUCTION

- Housing: 0.7mm CR4 steel
- Finish: Matt white
- ISO 7010 with all directional arrow options.
- IP20
- IP65

ENVIRONMENTAL

- Designed to allow simple replacement of components with commonly available tools in compliance with the Eco Design Directive, please see the installation leaflet for maintenance instructions.
- Powered by European branded drivers and emergency modules ensuring replacement parts are easily sourced.
- Every luminaire is labelled with a unique ID number allowing easy identification of spare parts for the lifetime of the product.
- Contains no single use plastics or polystyrene packaging.
- Supplied in plain card boxes with paper tape ensuring packaging is easily recycled.
- Designed to allow simple disassembly for end of life recycling.
- UK based manufacturing providing local support throughout the product lifetime and minimising transportation miles.

EMERGENCY

- Available with optional standard, self test and autotest integral emergency with lithium batteries for extended warranty and lifetime.
- Optional Reacta-Link wireless emergency for automated centralised reporting.
- Optional Reacta-Control wireless emergency for automated centralised reporting.
- Optional central battery changeover relay

INSTALLATION

- Suitable for conduit installation
- Suitable for surface installation



IMAGES

PRODUCT IMAGES



EXIXL

TECHNICAL



WARRANTY

At Dextra our commitment to service has been at the forefront throughout our history spanning more than forty years in the UK lighting market. Our service ethos extends beyond design and delivery, we believe supporting your installation throughout the warranty period is equally crucial, whilst the strength and longevity of Dextra Group provides peace of mind

that our warranty will be supported throughout.

The Dextra range is supplied with a five year warranty commencing from the date of delivery. During the first three years defects will be repaired on site and the warranty will include both parts and labour. For the final two years drivers, emergency modules, wireless modules, sensors and LED circuits will be supplied free of charge to replace defective components, labour and other associated costs are not included.

Certain ranges and components are subject to exemptions:

- Lithium batteries are provided with a three year warranty for parts and labour. Nickel Metal Hydride and Nickel Cadmium batteries are provided with a one year warranty for parts and labour.
- Emergency luminaires including AME LED, EXI LED, EXI2 LED, EXI Track, HBE LED, HBE2 LED, OAT2 LED, OEZ LED and Twinspot with Nickel Metal Hydride batteries are supplied with a one year warranty for parts and labour. Lithium variants of these ranges are supplied with a three year warranty for parts and labour with the exception of the AME2, EXI3, HBE3 and TWS IP65 L7 ranges which are supplied with a one year parts and labour warranty. TWS IP65 L7 in autotest and wireless variants are supplied with the standard three year lithium battery warranty.
- Protec Micro, PTECF7 Fire Rated Downlights, Serenus and the Opus Sconce are provided with a five year replacement luminaire only warranty. Protec FR Fire Rated Downlights are provided with a 2 year replacement luminaire only warranty.
- Controls systems such as standalone sensors, switches, marshalling boxes and cabling are provided with a one year warranty for both parts and labour. DALI control systems are provided with a two year warranty for both parts and labour.
- LEDextra ranges are supplied with a three year parts or replacement luminaire only warranty with the exception of the IMPR RGBW, the Runway RGBW, the MOD RGBW and the Tanek RGBW. These three ranges are supplied with our standard five year warranty during which defects within the first three years will be repaired on site and the warranty includes both parts and labour. For the final two years free of charge replacement components only will be supplied to rectify any failures but labour and other associated costs are not included.
- LEDEX ranges are supplied with a three year replacement luminaire only warranty.
- The Decorative Pendant ranges, Bebo, Dene, Nova, Fino and Stix are supplied with a 3 year replacement luminaire only warranty.

All warranties are subject to correct use of the product and will be invalidated by misuse, for example incorrect installation, unsuitable environmental conditions or incorrect maintenance. It is the duty of the customer to ensure that all the fault lies with the luminaire prior to requesting replacement parts or site repairs. In the event that no defect is found with the product our costs for attending site will be recharged to the customer and credit will not be issued against returned products. No consequential losses incurred resulting from any defect with our product will be reimbursed.

Given the nature of LED technology a small percentage of LEDs may fail during the lifetime of a luminaire, this does not cause a reduction in lumen output. As such LED luminaires are only deemed to be faulty for warranty purposes when in excess of ten percent of LEDs have failed in a single luminaire

On site repair of products under warranty will be undertaken during normal working hours, 9am to 5pm Monday to Friday, and will require unrestricted access to luminaires. Where required Dextra will provide access equipment to carry out repairs at height, should luminaires have been installed in locations where reasonable provision for maintenance access has not been made we reserve the right to supply replacement product only.

If you require any assistance with regards to our products please contact our Customer Services department on 01747 858100.

[DOWNLOAD WARRANTY PDF](#)

ORDER CODES

LUMINAIRE

Code	Description
EXIXL NM3 IP20 LE3 *	EXIXL 79M Viewing Distance, Non Maintained, IP20, Standard Emergency 3 Hour
EXIXL NM3 IP20 LS3 *	EXIXL 79M Viewing Distance, Non Maintained, IP20, Self Test Emergency 3 Hour
EXIXL NM3 IP20 LA3 *	EXIXL 79M Viewing Distance, Non Maintained, IP20, Autotest Emergency 3 Hour
EXIXL NM3 IP65 LE3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Standard Emergency 3 Hour
EXIXL NM3 IP65 LS3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Self Test Emergency 3 Hour
EXIXL NM3 IP65 LA3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Autotest Emergency 3 Hour
EXIXL NM3 IP65 HNE3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Standard Emergency 3 Hour, -25°C
EXIXL NM3 IP65 HNS3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Self Test Emergency 3 Hour, -25°C
EXIXL NM3 IP65 HNA3 *	EXIXL 79M Viewing Distance, Non Maintained, IP65, Autotest Emergency 3 Hour, -25°C

*Add legend code required

CONTROL

Code	Description
M3	Maintained

EMERGENCY

Code	Description
LSTR	Lithium Reacta-Link Emergency 3 Hour
LA3RC	Lithium Reacta-Control Emergency 3 Hour
CB	Central Battery, Please Specify 50V, 110V or 230V when Ordering

MISCELLANEOUS

Code	Description
LSF	Low Smoke Zero Halogen
DL	Arrow Down Legend ISO7010
LL	Arrow Left Legend ISO7010
RL	Arrow Right Legend ISO7010
UL	Arrow Up Legend ISO7010